

TECHNICAL DATA SHEET

HYDROCARBON SANOFRESH

CHARACTERISTICS

Special dry-cleaning detergent for hydrocarbon solvents

Optimal cleaning effect

Prevents greying

Reliable, proven and widespread deodorising effect in the complete system

High water-binding capacity

Pronounced anti-static finish

Can also be applied for pre-brushing

APPLICATION AND DOSAGES

Application:

Stock liquor:

2 – 3 ml/L liquor

Topping-up additive:

1% of weight of textiles

Depending on the type of machine and the process technology, the following dosages have proven to be of good results:

Liquor regeneration by distillation of the centrifugal part (approx. 25%):

30 – 50 ml Hydrocarbon Sanofresh per 10 kg textiles .

During intensive pre-spotting with Hydrocarbon Pre the lower value should be applicable.

Liquor regeneration by distillation of the 1st bath (approx. 50%) similar to the 2-bath method:

100 ml Hydrocarbon Sanofresh per 10 kg textiles into the 2nd bath

Application of Hydrocarbon Sanofresh as pre-brushing agent:

If Hydrocarbon Sanofresh is used for pre-brushing, it should be diluted 1:1 to 1:5 with hydrocarbon solvent.

Le nostre circolari servono esclusivamente a dare informazioni generali sull'uso dei nostri prodotti. Si consiglia di vagliare responsabilmente qualsiasi influenza possa verificarsi sui capi. Le ns. indicazioni riflettono le ns. cognizioni tecniche più aggiornate, ciò non implica alcuna garanzia legale da parte nostra. Caratteristiche e dati possono subire variazioni senza preavviso da parte nostra.

G.B.M. Electrochimica S.R.L.

Sede Legale – Via Fiumicino San Mauro 120/130 – 47039 Savignano sul Rubicone (FC)

Tel. 0541 930058 r.a. – Fax Comm. 0541 810218 - Fax Amm.ne 0541 815280 - www.gbmprodottichimici.it - gbm@gbmprodottichimici.it

Capitale Sociale € 20.000,00 i.v. - Cod. Fisc. e P.Iva 00958710402 – R.E.A. 192182

TECHNICAL DATA SHEET

TECHNICAL DATA

Density 20°C:	0,91 g/ml
pH-value:	7,0 - 8,0
Ionogenity:	anionic
Flashpoint:	62°C

Contents:

Anionic, non-ionic surfactants, preservatives, dissolved in hydrocarbon solvents.

DIRECTIONS

Store containers cool and tightly closed. If sealed in original packing the product can be stored for at least 24 months.

Le nostre circolari servono esclusivamente a dare informazioni generali sull'uso dei nostri prodotti. Si consiglia di vagliare responsabilmente qualsiasi influenza possa verificarsi sui capi. Le ns. indicazioni riflettono le ns. cognizioni tecniche più aggiornate, ciò non implica alcuna garanzia legale da parte nostra. Caratteristiche e dati possono subire variazioni senza preavviso da parte nostra.

G.B.M. Elettrochimica S.R.L.

Sede Legale – Via Fiumicino San Mauro 120/130 – 47039 Savignano sul Rubicone (FC)
Tel. 0541 930058 r.a. – Fax Comm. 0541 810218 - Fax Amm.ne 0541 815280 - www.gbmprodottichimici.it - gbm@gbmprodottichimici.it
Capitale Sociale € 20.000,00 i.v. - Cod. Fisc. e P.Iva 00958710402 – R.E.A. 192182